

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Problem Image Mailbox.**

## INK JET CARTRIDGE

### FIELD OF THE INVENTION AND RELATED ART

The present invention relates to an ink jet  
5 cartridge comprising: a recording head which records  
an image by ejecting ink; and an ink container in  
which the ink to be supplied to the recording head is  
stored. It also relates to an ink jet recording  
apparatus employing such an ink jet cartridge. In  
10 particular, it relates to an ink jet cartridge  
reliable in that it is structured so that its ink  
container can be reliably refilled with ink as  
necessary, and also, so that the performance of its  
recording head can be reliably restored as necessary,  
15 and also, it relates to an ink jet recording apparatus  
employing such an ink jet cartridge.

From the standpoint of reducing ink jet  
printer size, and also, the standpoint of reducing the  
load which is borne by the carriage of a printer,  
20 various proposals have been made. One of such  
proposals regards a method in which an ink jet  
cartridge is intermittently refilled with ink (which  
hereinafter may be simply referred to as pit-stop  
refill). According to this method, a printer is  
25 provided with a small ink container, or a subordinate  
container, and a large main ink container. The  
subordinate ink container is mounted on the carrier

along with a recording head, whereas the large main ink container is disposed within the printer, but not mounted on the carriage. In operation, the subordinate ink container, or the small ink container, is intermittently connected with the main ink container, and is refilled with the ink from the main ink container, as necessary, at a predetermined location.

A pit-stop refilling method can reduce the load which weighs down the carriage, making it thereby possible to move the carriage at a higher speed. In addition, according to the pit-stop refilling method, an ink jet recording apparatus is provided with the main ink container from which ink is supplied to the subordinate ink container. Therefore, the total amount of the ink mountable in the ink jet recording apparatus can be increased as much as possible, without affecting the amount of the load which weighs down on the carriage, as long as the internal space of the apparatus affords it. Further, the subordinate ink container does not need to be always connected to the main ink container, making it possible to substantially simplify an ink jet recording apparatus in structure.

As for a typical ink jet cartridge employing a pit-stop ink refilling method such as the one described above, the ink jet cartridge disclosed in

Japanese Laid-open Patent Application 200-334982 can be listed. In the case of the ink jet cartridge in Japanese Laid-open Patent Application 200-334982, ink can be pulled into the ink jet cartridge through the ink inlet thereof, by the negative pressure generated in the ink jet cartridge through the suction hole thereof. The suction hole is provided with a gas permeable member, that is, a member which allows gas to pass through while preventing liquid from doing so. Thus, as the body of ink having been suctioned into the ink jet cartridge reaches the gas-permeable member, it becomes impossible to continue the suction of the ink jet cartridge. In other words, the gas-permeable member plays the role of a fill-up check valve; it stops the ink refilling process.

As described above, in the case of the ink jet cartridge in accordance with the prior arts, as the ink jet cartridge is suctioned through the suction hole thereof in order to refill the ink jet cartridge by drawing ink into the ink jet cartridge, the gas-permeable member is deformed toward the suction hole by the negative pressure generated by the suction, as shown in Figure 4(a). Also in the case of the ink jet cartridge in accordance with the prior arts, as the ink jet cartridge, the recording head of which has been clogged with ink, is suctioned to restore the performance of the recording head, the gas-permeable

member is deformed toward the ink storage portion by the negative pressure generated by the suction, as shown in Figure 4(b). The operation for refilling the ink jet cartridge with ink, and the operation for restoring the performance of the ink jet cartridge, are repeated a substantial number of times, that is, from hundreds to as high as thousands of times, for the duration of the service life of the ink jet cartridge, and as the ink refilling operation, and/or performance recovery operation, is repeated hundreds to thousands of times, the gas-permeable member is repeatedly deformed the same number of times toward the suction hole or the liquid storage portion, being thereby mechanically deteriorated. Thus, the ink jet cartridge in accordance with the prior arts sometimes creates the situation in which ink leaks through the gas-permeable member due to the above described mechanical deterioration of the gas-permeable member.

#### SUMMARY OF THE INVENTION

The present invention was made to solve the above described problem, and its primary object is to provide a reliable ink jet cartridge of a pit-stop ink refill type, which is reliable in that its gas-permeable member is less likely to be deteriorated by the repetition of the cartridge suction necessary for refilling the ink jet cartridge and restoring the

performance of the ink jet cartridge, and therefore,  
less likely to leak ink due to the deterioration of  
the gas-permeable member, and also to provide an ink  
jet recording apparatus employing such an ink jet  
5 cartridge.

The present invention is characterized in  
that for the purpose of accomplishing the above  
object, an ink jet cartridge is provided with: an ink  
jet recording head; an ink container for storing the  
10 ink to be supplied to the recording head; a connective  
portion connectible to an ink supply source to make  
the ink container refillable with ink; a connective  
portion connectible to a pressure reduction source to  
reduce the internal pressure of the ink container to  
15 refill the ink container with ink; an absorbent member  
capable of holding ink, and disposed, as a source for  
providing the recording head with a certain amount of  
negative pressure, within the ink container; a gas-  
permeable member, that is, a member which allows gas  
20 to pass through, but does not allow liquid to do so,  
disposed between the absorbent member and the pressure  
reduction connective portion; and a pair of holding  
members which are partially in contact with the inward  
and outward surfaces, one for one, of the gas-  
25 permeable member, and hold the gas-permeable member.

The above described gas-permeable member is  
desired to be a porous member formed of poly-

tetrafluoroethylene or a substance similar in properties thereto.

According to another characteristic aspect of the present invention, the gas-permeable member is  
5 processed for water repellence.

According to another characteristic aspect of the present invention, an ink jet recording apparatus comprises:

a carriage, on which an ink jet cartridge  
10 comprising: an ink jet recording head; an ink container for storing the ink to be supplied to the recording head; a first connective portion connectible to an ink supply source to make the ink container refillable with ink; a second connective portion  
15 connectible to a pressure reduction source to reduce the internal pressure of the ink container to refill the ink container with ink; an absorbent member capable of holding ink, and disposed, as a source for providing the recording head with a certain amount of  
20 negative pressure, within the ink container; a gas-permeable member, that is, a member which allows gas to pass through, but does not allow liquid to do so, disposed between the absorbent member and the second connective portion; and a pair of holding members  
25 which are partially in contact with the inward and outward surfaces, one for one, of the gas-permeable member, and hold the gas-permeable member, is mounted;

an ink supply source which can be connected to, or disconnected from, the first connective portion of the ink container by a connective tube;

5 a negative pressure source which can be connected to, or disconnected from, the second connective portion of the ink container by a connective tube; and

10 a suctioning means connectible to the recording head to restore the performance of the recording head by suction.

These and other objects, features, and advantages of the present invention will become more apparent upon consideration of the following description of the preferred embodiments of the present invention, taken in conjunction with the  
15 accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

20 Figure 1 is a sectional view of the ink jet cartridge in the first embodiment of the present invention.

Figures 2(a) - 2(d) are plan views of the essential components of the ink jet cartridge in Figure 1, as seen from the direction indicated by an  
25 arrow mark A in Figure 1, showing them individually, one for one.

Figure 3 is a schematic drawing for



describing the pit-stop refilling of the ink jet cartridge with ink, in the first embodiment.

Figure 4 is a schematic drawing for describing the pit-stop refilling of the ink jet cartridge with ink, in accordance with the prior arts.

Figures 5(a) - 5(d) are plan views of various gas-permeable member holding members employable by the ink jet cartridge in the second embodiment to hold the gas-permeable member thereof.

Figures 6(a) and 6(b) are drawings for showing the gas-permeable member holding members different in structure from those shown in Figures 5(a) - 5(d).

Figure 7 is a schematic sectional view of the ink jet cartridge in the third embodiment of the present invention.

Figures 8(a) - 8(c) are plan views of the essential components of the ink jet cartridge in Figure 8, as seen from the direction indicated by an arrow mark D in Figure 6, individually showing them.

Figure 9 is a schematic sectional view of the ink jet cartridge in the fourth embodiment of the present invention.

Figures 10(a) - 10(b) are sectional views of the gas-permeable member of the ink jet cartridge in the fifth embodiment of the present invention.

Figure 11 is a schematic sectional view of

the ink jet cartridge in the sixth embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

5            Hereinafter the preferred embodiments of the present invention will be described.

(Embodiment 1)

          Figure 1 is a sectional view of the ink jet cartridge in the first embodiment of the present  
10          invention.

          Designated by a referential numeral 1 is an ejection unit for liquid ejection. As the recording head becomes clogged with ink, the liquid ejection orifices of the recording head are capped with a  
15          suction cap, that is, a head cap. Designated by a referential numeral 2 is a liquid storage chamber in which the liquid to be supplied to the ejection unit is stored (hereinafter, the liquid to be ejected from the recording head in this embodiment will be referred  
20          to as ink). The liquid storage chamber 2 is filled with a piece of absorbent substance (unshown) for absorbing ink and retaining it therein. A referential numeral 3 designates a liquid inlet to be connected with a main liquid container (unshown), and a  
25          referential numeral 4 designates an intermediary lid for sealing the liquid storage chamber 2. A referential numeral 5 designates a gas-permeable

member, and a referential numeral 6 designates a gas-permeable member holding (backing) member for holding down the gas-permeable member 5. A referential numeral 7 designates a gas-permeable member holding (backing) member for holding up the gas-permeable member 5, and a referential numeral 8 designates a top lid attached to the intermediary lid 4. A referential numeral 9 designates an air vent to be connected to a suction pump. The gas-permeable member 5 in this embodiment is a porous member.

Figures 2(a) - 2(d) are plan views of the essential components, one for one, of the ink jet cartridge in this embodiment, as seen from the direction indicated by an arrow mark A in Figure 1; (a) - (d) showing the gas-permeable member holding member 6, gas-permeable member holding member 7, gas-permeable member 5, and intermediary lid 4, respectively.

Referring to Figures 1 and 2, the intermediary lid 4 is provided with a hole, and the gas-permeable member 5 is placed in the recess of the intermediary lid 4, covering the hole of the intermediary lid 4. The gas-permeable member holding members 6 and 7 are formed of porous material, and are disposed in contact with the gas-permeable member 5, across the top and bottom surfaces, respectively. These gas-permeable member holding members 6 and 7

each are provided with a certain number of holes.

Figure 3 is a drawing for describing the pit-stop refilling of the ink jet cartridge with ink, in this embodiment.

5           Referring to Figure 3, ink is flowed  
(supplied) into the liquid storage chamber 2 through  
the liquid inlet 3, by suctioning (B) air out of the  
liquid storage chamber 2 through the air vent 9 with  
the use of a suction pump. There is the gas-permeable  
10 member holding member 6 on the gas-permeable member 5.  
Therefore, as the pressure is applied to the gas-  
permeable member 5 by the suction (D), the gas-  
permeable member holding member 6 backs up the gas-  
permeable member 5, reducing thereby the effects the  
15 pressure resulting from the suction (B). Therefore,  
virtually no change occurs to the shape of the gas-  
permeable member 5. Also referring to Figure 3, when  
it is necessary to unclog the ink jet cartridge to  
restore the performance of the recording head, the  
20 liquid storage chamber 2 is suctioned (C) by a suction  
pump through the ejection unit 1. In this case, as  
pressure applies to the gas-permeable member due to  
the suction (C), the gas-permeable member holding  
member 7 under the gas-permeable member 5 backs up the  
25 gas-permeable member 5, bearing a part of the  
pressure. Therefore, virtually no deformation occurs  
to the gas-permeable member.

Figures 4(a) and 4(b) are schematic sectional views of a comparative ink jet cartridge, that is, an ink jet cartridge which does not have the gas-permeable member holding member 6, showing how the ink jet cartridge is supplied with ink during a pit-stop refill.

Referring to Figure 4(a), ink is flowed (supplied) into the liquid storage chamber 2 by suctioning the liquid storage chamber 2 by a suction pump through the air vent 8. In the case of this ink jet cartridge, however, there is no gas-permeable member holding member 6 on the gas-permeable member 5. Therefore, the entirety of the pressure generated by the suction pump is borne by the gas-permeable member 5 alone, deforming thereby the gas permeable member 5. This deformation of the gas-permeable member 5 occurs each time the ink jet cartridge is refilled. Thus, if the ink jet cartridge is repeatedly refilled with ink, the gas-permeable member 5 deteriorates, making it possible for the ink to leak through the gas-permeable member 5.

Next, referring to Figure 4(b), when it is necessary to unclog the ink jet cartridge in order to restore the performance of the recording head, the ink storage chamber 2 is suctioned (E) by a suction pump through the ejection unit 1. In the case of this ink jet cartridge, there is no gas-permeable member

holding member 7 under the gas-permeable member 5.  
Therefore, the entirety of the pressure generated by  
the suction (E) is borne by the gas-permeable member 5  
alone, deforming thereby the gas-permeable member 5.  
5 Thus, if this ink jet cartridge is repeatedly refilled  
with ink, the gas-permeable member 5 deteriorates,  
making it possible for the ink to leak through the  
gas-permeable member 5.

(Embodiment 2)

10 The sectional view of the ink jet cartridge  
in this second embodiment of the present invention is  
similar to the sectional view of the ink jet cartridge  
shown in Figure 1; the ink jet cartridge in this  
embodiment is virtually the same as that in the first  
15 embodiment, except for the configurations of the gas-  
permeable member holding members 6 and 7. Figures  
5(a) - 5(d) show various patterns feasible as the  
configuration for the gas-permeable member holding  
member 6 or 7, as seen from the direction indicated by  
20 the arrow mark A or an arrow mark A' in Figure 1.

The gas-permeable member holding member 6  
shown in Figure 5(a) is not provided with a hole, but  
is formed of porous material, allowing thereby gaseous  
substance to easily pass through it.

25 The gas-permeable member holding member 6  
shown in Figure 5(b) has elongated holes which extend  
in the lengthwise direction of the ink jet cartridge.

The gas-permeable member holding member 6 shown in Figure 5(c) has a compound hole, which is a combination of a single long elongated hole parallel to the lengthwise direction of the ink jet cartridge, and a certain number of short elongated holes disposed in parallel, with equal intervals, in the direction perpendicular to the long elongated hole.

The gas-permeable member holding member 6 shown in Figure 5(d) has a long and narrow hole extending in an apparent zigzag pattern.

Shown in Figure 6 are additional structures for the gas-permeable member holding member 6 or 7.

Figure 6(a1) shows the lattice-like structure feasible for the gas-permeable member holding members 6 and 7, as seen from the direction indicated by an arrow mark A or A' in Figure 1, and Figure 6(a2) is a sectional view of the lattice-like structure feasible for the gas-permeable member holding members 6 and 7. In the case of this structure, the bottom surface of each of the strips extending in parallel in the direction perpendicular to the lengthwise direction of the ink jet cartridge is in contact with the top surface of each of the strips extending in the lengthwise direction of the ink jet cartridge.

Figure 6(b) is a schematic plan view of the structure feasible also for the gas-permeable member holding members 6 and 7, as seen from the direction

indicated by the arrow mark A or 'A' in Figure 1. In the case of this structure, the strips extending in parallel in the direction perpendicular to the lengthwise direction of the ink jet cartridge, and the strips extending in the lengthwise direction of the ink jet cartridge, are much narrower than the counterparts in Figure 6(a), and the former are perpendicular to the latter, effecting a mesh-like pattern.

No matter which of the structures shown in Figures 5 and 6 is employed as the structure for the gas-permeable member holding members 6 and 7, the substantial portion of the pressure which applies to the gas-permeable member 5 during the pit-stop refilling of the ink jet cartridge, or unclogging of the ink jet cartridge, is borne by the gas-permeable member holding member 6 or 7, substantially reducing thereby the stress to which the gas-permeable member 5 is subjected by the pressure, virtually eliminating the deformation of the gas-permeable member 5.

(Embodiment 3)

Figure 7 is a schematic sectional view of the ink jet cartridge in the third embodiment of the present invention.

Designated by a referential numeral 1 is an ejection unit for liquid ejection, and designated by a referential numeral 2 is a liquid storage chamber in



which the liquid to be supplied to the ejection unit is stored (hereinafter, the liquid to be ejected from the recording head in this embodiment will be referred to as ink). The liquid storage chamber 2 is filled with a piece of absorbent substance (unshown) for absorbing ink and retaining it therein. A referential numeral 3 designates a liquid inlet to be connected with a main liquid container (unshown), and a referential numeral 4 designates an intermediary lid for keeping the liquid storage chamber 2 virtually sealed. A referential numeral 5 designates a gas-permeable member, and a referential numeral 6 designates a holding member for holding down the gas-permeable member 5. A referential numeral 7 designates a holding member for holding up the gas-permeable member 5, and a referential numeral 8 designates a top lid attached to the intermediary lid 4. A referential numeral 9 designates an air vent to be connected to a suction pump. The gas-permeable member 5 in this embodiment is a porous member.

Figures 8(a) - 8(c) are plan views of the essential components of the ink jet cartridge in this embodiment, as seen from the direction indicated by an arrow mark D or D' in Figure 7; (a-1) and (a-2) showing the gas-permeable member holding members 6 and 7, respectively, and (b) and (c) showing the gas-permeable member 5 and intermediary lid 4,

respectively.

Referring to Figures 7 and 8, the intermediary lid 4 has three holes which lead to the three liquid storage chambers (unshown), and holds  
5 three gas-permeable members 5, blocking the three holes thereof. Further, the ink jet cartridge has two gas-permeable member holding members 6 and 7, which are disposed in contact with the top and bottom surfaces, respectively, of each of the gas-permeable  
10 members 5, holding down, and holding up, the gas permeable members 5, respectively. The gas-permeable member holding members 6 and 7 in this embodiment are provided with a certain number of holes.

In this embodiment, two gas-permeable member  
15 holding members 6 and 7 are provided for multiple (three in this embodiment) gas-permeable members 5. However, the effect of this structural arrangement is the same as that in the first embodiment; the substantial portion of the pressure which applies to  
20 the gas-permeable members 5 during the pit-stop refilling of the ink jet cartridge is borne by the gas-permeable member holding members 6 or 7, substantially reducing the amount of the stress to which the gas-permeable member is subjected by the  
25 pressure, virtually eliminating the deformation of the gas-permeable member 5.  
(Embodiment 4)

Figure 9 is a schematic sectional view of the ink jet cartridge in the fourth embodiment of the present invention.

Designated by a referential numeral 1 is an ejection unit for liquid ejection, and designated by a referential numeral 2 is a liquid storage chamber in which the liquid to be supplied to the ejection unit is stored (hereinafter, the liquid to be ejected from the recording head in this embodiment will be referred to as ink). The liquid storage chamber 2 is filled with a piece of absorbent substance (unshown) for absorbing ink and retaining it therein. A referential numeral 3 designates a liquid inlet to be connected with the main liquid container (unshown), and a referential numeral 4 designates an intermediary lid for keeping the liquid storage chamber 2 virtually sealed. A referential numeral 5 designates a gas-permeable member, which is in the recess of the intermediary lid 4. A referential numeral 6 designates a gas-permeable member holding member for holding down the gas-permeable member 5. A referential numeral 7 designates a gas-permeable member holding member for holding up the gas-permeable member 5, and a referential numeral 8 designates a top lid attached to the intermediary lid 4. A referential numeral 9 designates an air vent to be connected to a suction pump. The gas-permeable member 5 in this

embodiment is formed of porous material.

Referring to Figure 9, the gas-permeable member holding members 6 and 7 in this embodiment each are provided with a certain number of grooves, which  
5 are disposed in parallel in the direction perpendicular to the lengthwise direction of the ink jet cartridge. The gas permeable member holding members 6 and 7 in this embodiment are formed of porous material. Also in the case of this embodiment,  
10 the substantial portion of the pressure which applies to the gas-permeable members 5 during the pit-stop refilling of the ink jet cartridge is borne by the gas-permeable member holding member 6 or 7, substantially reducing the amount of the stress to  
15 which the gas-permeable member 5 is subjected by the pressure, virtually eliminating the deformation of the gas-permeable members 5, as in the case of the first embodiment.

(Embodiment 5)

20 The sectional view of the ink jet cartridge in the sixth embodiment of the present invention is virtually identical to Figure 9. Figure 10, which is a sectional view, shows only the portions of the ink jet cartridge in this embodiment, equivalent to the  
25 gas-permeable member holding member 6 or 7 shown in Figure 9. In other words, the ink jet cartridge in this embodiment is virtually identical to that shown

in Figure 9, except for the gas-permeable member holding members 6 and 7.

The gas-permeable member holding members 6 and 7 shown in Figure 10(a) are provided with a certain number of grooves with a predetermined depth, which are in the top and bottom surfaces thereof, and are in parallel to the direction perpendicular to the lengthwise direction of the ink jet cartridge.

The gas-permeable member holding members 6 and 7 shown in Figure 10(b) have a certain number of grooves, which are semicircular in vertical section.

The gas-permeable member holding members 6 and 7 shown in Figure 10(c) are shaped so that they look wavy in vertical section.

Also in this embodiment, no matter which of the gas-permeable member holding members 6 and 7 shown in Figures 10(a) - (c) is employed, the substantial portion of the pressure which applies to the gas-permeable member 5 during the pit-stop refilling of the ink jet cartridge is borne by the gas-permeable member holding member 6 or 7, substantially reducing thereby the amount of the stress to which the gas-permeable member 5 is subjected by the pressure, virtually eliminating the deformation of the gas-permeable member 5.

(Embodiment 6)

Figure 11 is a schematic sectional view of

the ink jet cartridge in the sixth embodiment of the present invention.

Designated by a referential numeral 1 is an ejection unit for liquid ejection, and designated by a referential numeral 2 is a liquid storage chamber in which the liquid to be supplied to the ejection unit is stored (hereinafter, the liquid to be ejected from the recording head in this embodiment will be referred to as ink). The liquid storage chamber 2 is filled with a piece of absorbent substance (unshown) for absorbing ink and retaining it therein. A referential numeral 3 designates a liquid inlet to be connected with the main liquid container (unshown), and a referential numeral 4 designates an intermediary lid for keeping the liquid storage chamber 2 virtually sealed. A referential numeral 5 designates a gas-permeable member, which is in the recess of the intermediary lid 4. A referential numeral 6 designates a gas-permeable member holding member placed in contact with the bottom surface of the gas-permeable member 5. A referential numeral 7 designates a top lid attached to the intermediary lid 4, and a referential numeral 8 designates an air vent to be connected to a suction pump. The gas-permeable member 5 in this embodiment is a porous member.

In this embodiment, the top lid 7 is provided with a certain number of projections which are in

contact with the gas-permeable member 5. Thus, the top lid 7 also plays the role of gas-permeable member holding member while functioning as a top lid.

Also in the case of this embodiment, the  
5 substantial portion of the pressure which applies to the gas-permeable member 5 during the pit-stop refilling of the ink jet cartridge is borne by the gas-permeable member holding member 6 or 7, substantially reducing thereby the amount of the  
10 stress to which the gas-permeable member 5 is subjected by the pressure, virtually eliminating the deformation of the gas-permeable member 5.

In this embodiment, the top lid 7 is attached to the intermediary lid 4 so that it remains in  
15 contact with the gas-permeable member 5. However, there may be a gap between the top lid 7 and gas-permeable member 5, as long as the top lid 7 is positioned so that the substantial portion of the pressure which applies to the gas-permeable member 5  
20 during the pit-stop refilling of the ink jet cartridge with ink is borne by the top lid 7. Such placement of the top lid 7 is within the scope of the present invention.

As described above, according to the present  
25 invention, the substantial portion of the pressure which applies to the gas-permeable member of an ink jet cartridge during the pit-stop refilling of the ink

jet cartridge with ink is borne by the gas-permeable member holding member, substantially reducing the amount of the stress to which the gas-permeable member is subjected during the pit-stop refilling, reducing thereby the amount of the deformation of the gas-permeable member. Thus, the present invention makes it possible to provide a reliable and durable ink jet cartridge of a pit-stop refill type, which is reliable and durable in that it can be subjected to the pit-stop refill operation a substantially larger number of times without being affected in its performance, compared to a refillable ink jet cartridge in accordance with the prior arts.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth, and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.